

MEDIATEX® Grey Back Textile FR

	Einheit Unit	Norm Standard	Wert Value
Substrat Substrate		DIN 60001	100% Polyester 100% polyester
Bindung Weave		DIN ISO 9354	Gewebe woven fabric
Flächengewicht Weight	 g/m ²	DIN EN ISO 2286-2	290 ± 20
Schwerentflammbarkeit Flame retardant		DIN 4102 B1, ÖNORM A3800	ja yes
Tintentyp Type of ink		  	alle Solventtinten; UV-härt.*; Latextinten all kinds of solvent; UV-curable*; latex inks
Anwendung Application			innen indoor
Breite Width	 cm inch	DIN EN ISO 2286-1	max. 310 max. 122
Druckseite Print side			Breite < 3m: Druckseite außen Breite > 3m: Druckseite innen width < 3m: print side outside width > 3m: print side inside
Rollenlänge Roll length	 m		30 - 50 ± 0,5

Anwendungen Applications



Blockout / blackout
Display / display
Roll up / roll up
Banner / banner
Frontlit / frontlit
Messebau / trade show graphic
Rollo, Lamelle, Flächenvorhang /
roller, vertical, panel blinds

Besonderheiten Characteristics

- höchste Druckqualität
highest print quality
- kein Weißbruch
no white cracking / crazing
- kalt schneidbar
trimming cold
- leichte Montage
easy to mount
- schnelle Faltenherholung
fast crease recovery

* Da UV-härtende Tinten noch nachhärten, ist mit einem Schüsseln zu rechnen.

Please consider the risk of „curling“ because UV-curable inks will still be hardening after a while.

All details are nominal values and are subject to change within usual tolerances (± 5%). The information provided in this document is based on current knowledge and experience. They do not exempt a manufacturer/processor from carrying out their own tests and trials as their in-house handling and manufacturing processes can have a significant range of influences on outcomes. Application, utilisation and processing of products is taking place outside of our control and are therefore the sole responsibility of the manufacturer/processor. date: 05/2016